

Awning Window

The Urban Plus Awning Window incorporates clean, flat sash profiles within a bold outer frame to deliver a modern aesthetic with excellent strength and performance characteristics.

Available as top-hinged configurations to suit your application, the Urban Plus Awning Window takes a traditional and popular window style and brings it into the 21st century with considered design solutions for screening, operation, drainage and aesthetics. The Urban Plus Awning Window is an ideal choice for high-end architectural applications.





Awning Window





Features + Benefits

- Accepts double glazing up to 26mm alongside standard single glazing options
- Compatible with the full range of Urban Plus window suites
- · Custom designed hardware options
- AGS 300/325 and 400/425 Narrowline compatible for seamless integration
- Awning configurations incorporate an integrated hook hinge at the head for strength
- Integrated insect and security screening options for a modern, tidy aesthetic

Maximum Performance

| Serviceability Pressure | 1900Pa |
|-------------------------|--------|
| Ultimate Pressure | 4600Pa |
| Water Penetration | 1200Pa |

Frame Dimensions

| Depth | 76mm |
|-------|---------|
| рерии | /011111 |

Maximum Recommended Size

| Sash Height | 2100mm* |
|-------------|---------|
| Sash Width | 2100mm* |
| Sash Weight | 106kg |

Glazing Capacity

| Single Glazed | 4mm - 14mm |
|---------------|-------------|
| Double Glazed | 12mm - 26mm |

^{*}Maximum sash height and width are interdependent. The overall sash size cannot exceed an area of 1.9m.

Measurements

| Stud Opening | | 650 | 950 | 1250 | 1550 | 1850 | 2150 | 2450 | 2750 | 3050 |
|-----------------|---------------|-----|-----|------|------|------|------|-----------|------|------|
| | Frame Size | 600 | 900 | 1200 | 1500 | 1800 | 2100 | 2400 | 2700 | 3000 |
| 650 | 600 | | | | | | M | M | | |
| 950 | 900 | | | | | | M | \bigvee | | |
| 1250 | 1200 | | | | | | | | | |
| 1550 | 1500 | | | | | | | | | |
| 1850 | 1800 | | | | | | | | | |
| 1850 | 1800 | | | | | | | | | |
| 2150 | 2100 | | | | | | | | | |
| 2150 | 2100 | | | | | | | | | |



