

# Sliding Window

The Urban Plus Sliding Window delivers contemporary styling alongside, strength and performance making it an ideal solution for high-end architectural applications.

The system features embedded top and bottoms rail, delivering a modern panoramic design with crisp sight lines. Integrated insect screening maintains the sleek aesthetic and neat appearance of this system. Options to incorporate high performance insulated glass ensure excellent thermal outcomes whilst delivering an uninterrupted view of the outdoors.





## Sliding Window





#### Features + Benefits

- Panoramic Head and Sill design to maximise your view
- Integrated insect and security screening options for a tidy aesthetic
- Two and three track configurations
- 2 track: OX, XX, OXO, XOX, OXXO
- 3 track: OXX, XXX, OXXXXO
- AGS 300/325 and 400/425 Narrowline compatible for seamless integration
- High light and low light combinations to suit contemporary building requirements
- Accepts double glazing up to 18mm

#### **Maximum Performance**

Serviceability Pressure	3000Pa
Ultimate Pressure	7000Pa
Water Penetration	450Pa

#### Frame Dimensions (Depth)

Standard Frame	76mm
Multi-stack	101.6mm

#### **Maximum Recommended Size**

Sash Height	1800mm			
Sash Width	1800mm			
Sash Weight	60kg			

### **Glazing Capacity**

Single Glazed	4mm - 10mm
Double Glazed	16mm - 18mm

#### Measurements

Stud Opening		650	950	1250	1550	1850	2150	2450	2750	3050
	Frame Size	600	900	1200	1500	1800	2100	2400	2700	3000
650	600	<b>→</b>	$\rightarrow$	<b>→</b>	<b>—</b>	<b>←</b>	<b>—</b>	<b>→</b>	<b>→</b>	<b>→ ←</b>
950	900	<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>
1250	1200	<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→ ←</b>	<b>→</b>	<b>→</b>	<b>→</b>
1550	1500		<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→ ←</b>	<b>→</b> ←	<b>→</b>	+
1850	1800		<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>→ ←</b>	<b>→ ←</b>	<b>→</b> ←	+ +
2150	2100		<b>→</b>	<b>→</b>	<b>→</b>	<b>→</b>	<b>+</b>	<b>→</b> ←	<b>→</b> ←	+ +



